

---

# From Coil to Press: Intelligent Inline Monitoring of Strip Behaviour in Forming Processes

---

Ondřej Vitoslavský

# Our Projects

---

**AIStraight – In progress**

**SmartCushionPin – Completed**

# What can go wrong in sheet metal forming

- Thickness variations
- Flatness/waviness
- Residual stresses/tension
- Everything



**Wrinkling**



**Tearing**




**Unstable feeding**




**Springback**

# Monitor the strip along the whole process chain

- Without monitoring scrap rates up to **~15% in production**
- Goal is simple = Zero defect
- What is already measured?





# Thickness variations

---


- General strip thickness
- Controlled by AGC – Automatic Gauge Control
- Variation in forming forces
- Change in springback
- Double-checking before pressing machine



# Thickness variations




- Thickness profile across the width
- Mostly done offline
- Pressing machine overload
- Tool damage


Strip thickness profile



# Flatness and tension distribution

- Strip flatness
- Tension distribution across the width
- Waves in the strip
- Unstable feeding
- Uneven forming
- Asymmetric tool loading






**Straightening machine**

# What happens in a straightener

- Alternating bending between rolls
- Gradual reduction of curvature
- Manual adjustment
- $S_{final} = f(H, d, i, l)$
- $S_{final}$  = How does it look




# Vision: AI Straightening

---

- Concept
  - Sensor data from straightener
  - Information about material state
  - Process model or AI algorithm
- Goal
  - Automatic adjustment of roll settings


# What can be measured in the straightener

- Straightening forces
  - 3 possible places to measure
- Roll position/immersion




# Measuring material state inline

- Material strain
  - Laser Speckle Photometry [Fraunhofer]
  - Digital Image Correlation
- Residual stress
  - Barkhausen noise, LSP




stress → strain → surface deformation → speckle pattern change



**Pressing machine**

# Smart Cushion Pin

- Replacing standard cushion pin
- Measuring forces during metal sheet forming








IR node

Smart Cushion Pin

# Data collection/visualisation


- Up to 120 Smart cushion pins
- Up to 32 IR Nodes
- 400 Samples per second
- Up to 60 measurements per minute




# Single SmartCushionPin measurement



# Multiple SmartCushionPin measurements



**Thank you for your attention!**



**[www.uvbtechnik.cz](http://www.uvbtechnik.cz)**