






CFD-Based Digital Twin of a PEM Fuel Cell with AI-Driven Surrogate Modelling




Tomas Karasek
IT4Innovations, VSB TU Ostrava







Ministry of the Environment
of the Czech Republic











Anode

(Hydrogen Oxidation Reaction)






Cathode



(Oxygen Reduction Reaction)



Whole system







PEM Fuel Cell Model

Enable PEMFC

Model

Parameters

Anode

Electrolyte

Cathode

Electrical Tabs

Advanced

Customized UDFs

Reports

Options

- Joule Heating
- Reaction Heating
- Electrochemistry Sources
- Butler-Volmer Rate
- Multicomponent Diffusion
- Anisotropic E-Cond. in GDL/MPL
- Effective P-Cond. in MEA
- Use Half-Cell Potentials
- Cathode Particle Model
- Liquid Phase
- Compute Liquid in Channels
- Include Dynamic Head
- Knudsen Diffusion
- Temperature Dependent Jref
- N2 Crossover

W-Diff Model

Wu
 Wang

Automatic Settings

F-Cycle for All Equations

Electrical System Setup

Set Up in B.C. Panels
 Specify Total Voltage
 Specify Total Current

Under-Relaxation Factors

Liq.-Vap. Source:

Disv'd-Vap./Liq. Source:

Osmotic Drag Source:

GDL Liquid Removal:

OK
Apply
Reset
Cancel
Help

$$R_{an} = (\zeta_{an} j_{an}(T)) \left(\frac{[A]}{[A]_{ref}} \right)^{\gamma_{an}} \left(e^{\alpha_{an}^{an} F \eta_{an} / RT} - e^{-\alpha_{cat}^{an} F \eta_{an} / RT} \right)$$

$$j_{an}(T) = j_{an}^{ref} e^{-E_{an} / RT (1 - T / T_{an}^{ref})}$$

$E_{an} = 0$

| Electrochemistry | |
|---------------------|---------------------|
| Anode | Cathode |
| j_ref (A/m2) | j_ref (A/m2) |
| 10000 | 10 |
| C_ref (kmol/m3) | C_ref (kmol/m3) |
| 1 | 1 |
| Con. Exponent | Con. Exponent |
| 1 | 1 |
| Exch. Coeff.(a) | Exch. Coeff. (a) |
| 1 | 1 |
| Exch. Coeff.(c) | Exch. Coeff. (c) |
| 1 | 1 |
| Std. State E0(V) | Std. State E0 (V) |
| 0 | 1.22884 |
| Entropy (J/kgmol-k) | Entropy (J/kgmol-k) |
| 0 | -163300 |

$$R_{cat} = (\zeta_{cat} j_{cat}(T)) \left(\frac{[C]}{[C]_{ref}} \right)^{\gamma_{cat}} \left(e^{\alpha_{an}^{cat} F \eta_{cat} / RT} + e^{-\alpha_{cat}^{cat} F \eta_{cat} / RT} \right)$$

| Electrochemistry | | Liquid Phase | | Other Parameters | |
|---------------------|---------------------|------------------------|----------------------|---------------------|--|
| Anode | Cathode | Global | | | |
| j_ref (A/m2) | j_ref (A/m2) | I_leak (A/m2) | Expon't Diff_gas | Gas-Dis'ed Phase | |
| 10000 | 10 | 0 | 2.5 | 0.5 | |
| C_ref (kmol/m3) | C_ref (kmol/m3) | Std. Temp. for U0(K) | Expon't j_ref | Mod. Coef. OSM_drag | |
| 1 | 1 | 298.15 | 2.5 | 1 | |
| Con. Exponent | Con. Exponent | Std. Press. for U0(Pa) | Expon't K_rel | Eq. W. Cont. at a=1 | |
| 1 | 1 | 100000 | 3 | 9.2 | |
| Exch. Coeff.(a) | Exch. Coeff. (a) | | Expon't Liq_coverage | Eq. W. Cont. at s=1 | |
| 1 | 1 | | 1 | 16.8 | |
| Exch. Coeff.(c) | Exch. Coeff. (c) | | Liq-Dis'ed Phase | N2 Crossover Factor | |
| 1 | 1 | | 0.5 | 0.001 | |
| Std. State E0(V) | Std. State E0 (V) | | Liquid Density | | |
| 0 | 1.22884 | | 982 | | |
| Entropy (J/kgmol-k) | Entropy (J/kgmol-k) | | Liq. Thermal Cond. | | |
| 0 | -163300 | | 0.6 | | |
| | | | Liq. Diff. in Chan. | | |
| | | | 1e-05 | | |
| | | | V_liq/V_gas in Chan. | | |
| | | | 0.005 | | |

$$R_{cat} = (\zeta_{cat} j_{cat}(T)) \left(\frac{[C]}{[C]_{ref}} \right)^{\gamma_{cat}} \left(e^{\alpha_{an}^{cat} F \eta_{cat} / RT} + e^{-\alpha_{cat}^{cat} F \eta_{cat} / RT} \right)$$

| Electrochemistry | |
|---------------------|---------------------|
| Anode | Cathode |
| j_ref (A/m2) | j_ref (A/m2) |
| 10000 | 10 |
| C_ref (kmol/m3) | C_ref (kmol/m3) |
| 1 | 1 |
| Con. Exponent | Con. Exponent |
| 1 | 1 |
| Exch. Coeff.(a) | Exch. Coeff. (a) |
| 1 | 1 |
| Exch. Coeff.(c) | Exch. Coeff. (c) |
| 1 | 1 |
| Std. State E0(V) | Std. State E0 (V) |
| 0 | 1.22884 |
| Entropy (J/kgmol-k) | Entropy (J/kgmol-k) |
| 0 | -163300 |

$$D_i = \varepsilon^{1.5} (1 - s)^{r_s} D_i^0 \left(\frac{p_0}{p} \right)^{\gamma_p} \left(\frac{T}{T_0} \right)^{\gamma_t}$$

$$R_j = (1 - s)^{\gamma_j} R_j$$

$$K_r = s^b$$

$$S_{gd} = (1 - s^\theta) \gamma_{gd} M_{w,H_2O} \frac{\rho_i}{EW} (\lambda_{eq} - \lambda)$$

$$S_{ld} = s^\theta \gamma_{ld} M_{w,H_2O} \frac{\rho_i}{EW} (\lambda_{eq} - \lambda)$$

$$k_{eff} = s k_i + (1 - s) [\varepsilon k_{gas} + (1 - \varepsilon) k_{solid}]$$

| Liquid Phase | |
|----------------------|---------------|
| Expon't Diff_gas | r_s |
| 2.5 | |
| Expon't j_ref | γ_j |
| 2.5 | |
| Expon't K_rel | b |
| 3 | |
| Expon't Liq_coverage | θ |
| 1 | |
| Liq-Dis'ed Phase | γ_{ld} |
| 0.5 | |
| Liquid Density | ρ_l |
| 982 | |
| Liq. Thermal Cond. | k_i |
| 0.6 | |


| No. | Parameter Name | Symbol | Unit | Range (Dakota) | No. | Parameter Name | Symbol | Unit | Range (Dakota) |
|-----|--|------------------|---------------------|--|-----|---|----------------|-------------------|--|
| 1 | Reference current density (anode) | $J_{ref,an}$ | A/m ² | 1000, 10000, 20000 | 39 | CL (anode) permeability | K | m ² | 10 ⁻¹³ , 10 ⁻¹¹ , 10 ⁻⁹ |
| 2 | Reference current density (cathode) | $J_{ref,cat}$ | A/m ² | 1, 10, 20 | 40 | CL (anode) surface/volume ratio | ζ | 1/m | 10000, 200000, 1000000 |
| 3 | Reference molar concentration H ₂ (anode) | $C_{ref,an}$ | kmol/m ³ | 0.05, 1 | 41 | CL (anode) hydrophobic contact angle | θ_c | ° | 90, 110, 135 |
| 4 | Reference molar concentration O ₂ (cathode) | $C_{ref,cat}$ | kmol/m ³ | 0.01, 1 | 42 | CL (anode) activation energy for J_{ref} | E_i | J/kmol | 5E+06, 8.314E+06, 1.2E+07 |
| 5 | Concentration exponent (anode) | γ_{an} | - | 0.3, 0.65, 1.0 | 43 | CL (anode) reference temperature for J_{ref} | $T_{0,an}$ | K | 338 |
| 6 | Concentration exponent (cathode) | γ_{cat} | - | 0.3, 0.65, 1.0 | 44 | CL (anode) Leverett coeff. a | a | - | 1.417 |
| 7 | Transfer coefficient (anode) | α_{an} | - | 0.3, 0.65, 1.0 | 45 | CL (anode) Leverett coeff. b | b | - | 2.12 |
| 8 | Transfer coefficient (anode) | α_{an} | - | 0.3, 0.65, 1.0 | 46 | CL (anode) Leverett coeff. c | c | - | 1.263 |
| 9 | Transfer coefficient (cathode) | α_{cat} | - | 0.3, 0.65, 1.0 | 47 | CL (anode) condensation coeff. | γ_c | - | 1E+06, 1E+08, 1E+10 |
| 10 | Transfer coefficient (cathode) | α_{cat} | - | 0.3, 0.65, 1.0 | 48 | CL (anode) evaporation coeff. | γ_e | - | 1E+06, 1E+08, 1E+10 |
| 11 | Reversible potential (anode) | $U_{0,an}$ | V | 0 | 49 | Membrane equivalent weight | EW | kg/kmol | 800, 1100, 1250 |
| 12 | Reversible potential (cathode) | $U_{0,cat}$ | V | 1.229 | 50 | Membrane protonic conduction coeff. | β_{mem} | - | 0.5, 1, 2 |
| 13 | Entropy (anode) | ΔS_{an} | J/kmolK | -130000 | 51 | Membrane protonic conduction exponent | ω_i | - | 0.5, 1, 2 |
| 14 | Entropy (cathode) | ΔS_{cat} | J/kmolK | -32660 | 52 | Membrane water diffusivity coeff. | η_λ | - | 0.1, 1, 2 |
| 15 | Leakage current density | I_{leak} | A/m ² | 0 | 53 | Membrane permeability | K | m ² | 10 ⁻¹³ , 10 ⁻¹¹ , 10 ⁻⁹ |
| 16 | Standard temperature | T_0 | K | 298.15 | 54 | GDL (cathode) porosity | ϵ | - | 0.4, 0.75, 0.9 |
| 17 | Standard pressure | p_0 | Pa | 101325 | 55 | GDL (cathode) permeability | K | m ² | 10 ⁻¹³ , 10 ⁻¹¹ , 10 ⁻⁹ |
| 18 | Exponent Diffusion gas | r_s | - | 1.5, 2.5, 3.5 | 56 | GDL (cathode) hydrophobic contact angle | θ_c | ° | 90, 110, 135 |
| 19 | Exponent J_{ref} | γ_j | - | 1.5, 2.5, 3.5 | 57 | GDL (cathode) water removal coef. | Θ | s/m | 1E-05, 5E-05, 1E-04 |
| 20 | Exponent relative permeability | b | - | 2, 3, 4 | 58 | GDL (cathode) Leverett coeff. a | a | - | 1.417 |
| 21 | Exponent liquid coverage | θ | - | 0.2, 1, 1.8 | 59 | GDL (cathode) Leverett coeff. b | b | - | 2.12 |
| 22 | Liq.-Dissolved Phase | γ_{td} | - | 0.25, 0.5, 1, 1.5 | 60 | GDL (cathode) Leverett coeff. c | c | - | 1.263 |
| 23 | Liquid density | ρ_l | kg/m ³ | 982 | 61 | GDL (cathode) condensation coeff. | γ_c | - | 1E+06, 1E+08, 1E+10 |
| 24 | Liquid thermal conductivity | k_l | W/mK | 0.6 | 62 | GDL (cathode) evaporation coeff. | γ_e | - | 1E+06, 1E+08, 1E+10 |
| 25 | Gas-dissolved Phase | γ_{gd} | - | 0.25, 0.5, 0.75 | 63 | CL (cathode) porosity | ϵ | - | 0.4, 0.75, 0.9 |
| 26 | Osmotic drag coefficient | η_{osm} | - | 0.5, 1, 1.5 | 64 | CL (cathode) permeability | K | m ² | 10 ⁻¹³ , 10 ⁻¹¹ , 10 ⁻⁹ |
| 27 | Eq. water content at a=1 | λ_a | - | 9.2 | 65 | CL (cathode) surface/volume ratio | ζ | 1/m | 10000, 200000, 1000000 |
| 28 | Eq. water content at s=1 | λ_s | - | 16.8 | 66 | CL (cathode) hydrophobic contact angle | θ_c | ° | 90, 110, 135 |
| 29 | GDL (anode) porosity | ϵ | - | 0.4, 0.75, 0.9 | 67 | CL (cathode) activation energy for J_{ref} | E_i | J/kmol | 5E+06, 8.314E+06, 1.2E+07 |
| 30 | GDL (anode) permeability | K | m ² | 10 ⁻¹³ , 10 ⁻¹¹ , 10 ⁻⁹ | 68 | CL (cathode) reference temperature for J_{ref} | $T_{0,cat}$ | K | 343 |
| 31 | GDL (anode) hydrophobic contact angle | θ_c | ° | 90, 110, 135 | 69 | CL (cathode) product of O ₂ solubility | $K_w D_w$ | m ² /s | 1E-9, 1E-8, 1E-7 |
| 32 | GDL (anode) water removal coef. | Θ | s/m | 1E-05, 5E-05, 1E-04 | 70 | CL (cathode) catalyst particle radius | r_p | m | 1E-9, 5E-8, 1E-8 |
| 33 | GDL (anode) Leverett coeff. a | a | - | 1.417 | 71 | CL (cathode) ionomer resistance | R_{ion} | s/m | 50, 100, 300 |
| 34 | GDL (anode) Leverett coeff. b | b | - | 2.12 | 72 | CL (cathode) Leverett coeff. a | a | - | 1.417 |
| 35 | GDL (anode) Leverett coeff. c | c | - | 1.263 | 73 | CL (cathode) Leverett coeff. b | b | - | 2.12 |
| 36 | GDL (anode) condensation coeff. | γ_c | - | 1E+06, 1E+08, 1E+10 | 74 | CL (cathode) Leverett coeff. c | c | - | 1.263 |
| 37 | GDL (anode) evaporation coeff. | γ_e | - | 1E+06, 1E+08, 1E+10 | 75 | CL (cathode) condensation coeff. | γ_c | - | 1E+06, 1E+08, 1E+10 |
| 38 | CL (anode) porosity | ϵ | - | 0.4, 0.75, 0.9 | 76 | CL (cathode) evaporation coeff. | γ_e | - | 1E+06, 1E+08, 1E+10 |
| | | | | | 77 | Coolant density | ρ_c | kg/m ³ | 998.2 |

| No. | Parameter Name | Symbol | Unit | Range (Dakota) |
|-----|---|--------------------|---------------------|---------------------------|
| 1 | Reference current density (anode) | $J_{ref,an}$ | A/m ² | 1000, 10000, 20000 |
| 2 | Reference current density (cathode) | $J_{ref,cat}$ | A/m ² | 1, 10, 20 |
| 3 | Reference molar concentration H ₂ (anode) | $C_{ref,an}$ | kmol/m ³ | 0.05, 1 |
| 4 | Reference molar concentration O ₂ (cathode) | $C_{ref,cat}$ | kmol/m ³ | 0.01, 1 |
| 5 | Concentration exponent (anode) | γ_{an} | - | 0.3, 0.65, 1.0 |
| 6 | Concentration exponent (cathode) | γ_{cat} | - | 0.3, 0.65, 1.0 |
| 7 | Transport coefficient (anode) | α_{anode} | - | 0.3, 0.65, 1.0 |
| 8 | Transport coefficient (cathode) | $\alpha_{cathode}$ | - | 0.3, 0.65, 1.0 |
| 9 | Exponent: diffusion gas | r_s | - | 1.5, 2.5, 3.5 |
| 10 | Exponent: J_{ref} | γ_j | - | 1.5, 2.5, 3.5 |
| 11 | Exponent: relative permeability | b | - | 2, 3, 4 |
| 12 | Exponent: liquid coverage | θ | - | 0.2, 1, 1.8 |
| 13 | Exponent: liquid-dissolved phase | γ_{td} | - | 0.25, 0.5, 1, 1.5 |
| 14 | Exponent: gas-dissolved phase | γ_{gd} | - | 0.25, 0.5, 0.75 |
| 15 | Osmotic drag coefficient | η_{osm} | - | 0.5, 1, 1.5 |
| 16 | GDL/CL porosity | ϵ | - | 0.4, 0.75, 0.9 |
| 17 | GDL/CL absolute permeability | K | m ² | 1E-16, 1E-12, 1E-08 |
| 18 | GDL/CL hydrophobic contact angle | θ_c | ° | 90, 110, 135 |
| 19 | Water removal coefficient (GDL/CL) | Θ | s/m | 1E-05, 5E-05, 1E-04 |
| 20 | Condensation rate coefficient (GDL/CL) | γ_c | - | 1E+06, 1E+08, 1E+10 |
| 21 | Evaporation rate coefficient (GDL/CL) | γ_e | - | 1E+06, 1E+08, 1E+10 |
| 22 | Catalyst layer surface-to-volume ratio (anode) | ζ | 1/m | 10000, 200000, 1000000 |
| 23 | Activation energy for J_{ref} | E_i | J/kmol | 5E+06, 8.314E+06, 1.2E+07 |
| 24 | Membrane equivalent weight | EW | kg/kmol | 800, 1100, 1250 |
| 25 | Membrane protonic conduction coefficient | β_{mem} | - | 0.5, 1, 2 |
| 26 | Membrane protonic conduction exponent | ω_i | - | 0.5, 1, 2 |
| 27 | Membrane water diffusivity coefficient | η_λ | - | 0.1, 1, 2 |
| 28 | Cathode CL product of O ₂ solubility and diffusivity | $K_w D_w$ | m ² /s | 1E-9, 1E-8, 1E-7 |
| 29 | Cathode CL catalyst particle radius | r_p | m | 1E-9, 5E-8, 1E-8 |
| 30 | Cathode CL ionomer resistance | R_{ion} | s/m | 50, 100, 300 |

Variable



| No. | Parameter Name | Symbol | Unit | Fixed Value / Range |
|-----|--|------------------|-------------------|--|
| 1 | Reversible potential (anode) | $U_{0,an}$ | V | 0 |
| 2 | Reversible potential (cathode) | $U_{0,cat}$ | V | 1.229 |
| 3 | Entropy (anode) | ΔS_{an} | J/kmolK | -130000 |
| 4 | Entropy (cathode) | ΔS_{cat} | J/kmolK | -32660 |
| 5 | Leakage current density | I_{leak} | A/m ² | 0 |
| 6 | Standard temperature | T_0 | K | 298.15 |
| 7 | Standard pressure | p_0 | Pa | 101325 |
| 8 | Liquid density | ρ_l | kg/m ³ | 982 |
| 9 | Liquid thermal conductivity | k_l | W/mK | 0.6 |
| 10 | Eq. water content at a = 1 | λ_a | - | 9.2 |
| 11 | Eq. water content at s = 1 | λ_s | - | 16.8 |
| 12 | GDL (anode) Leverett coefficient a | a | - | 1.417 |
| 13 | GDL (anode) Leverett coefficient b | b | - | 2.12 |
| 14 | GDL (anode) Leverett coefficient c | c | - | 1.263 |
| 15 | CL (anode) reference temperature for J_{ref} | $T_{0,an}$ | K | 338 |
| 16 | CL (anode) Leverett coefficient a | a | - | 1.417 |
| 17 | CL (anode) Leverett coefficient b | b | - | 2.12 |
| 18 | CL (anode) Leverett coefficient c | c | - | 1.263 |
| 19 | Membrane permeability | K | m ² | 10 ⁻¹³ , 10 ⁻¹¹ , 10 ⁻⁹ |
| 20 | GDL (cathode) Leverett coefficient a | a | - | 1.417 |
| 21 | GDL (cathode) Leverett coefficient b | b | - | 2.12 |
| 22 | GDL (cathode) Leverett coefficient c | c | - | 1.263 |
| 23 | CL (cathode) reference temperature for J_{ref} | $T_{0,cat}$ | K | 343 |
| 24 | CL (cathode) Leverett coefficient a | a | - | 1.417 |
| 25 | CL (cathode) Leverett coefficient b | b | - | 2.12 |
| 26 | CL (cathode) Leverett coefficient c | c | - | 1.263 |
| 27 | Coolant density | ρ_c | kg/m ³ | 998.2 |


Fixed






Find the set of parameters P corresponding to the volt-ampere characteristic.

$\{(U_j, I_j)\}$
for $j \in \{1, 2, 3\}$.








- Random initialisation of parameters P (50 configurations)
- Gradient optimisation method (Adam: learning rate 1e-3)
- Selected 15 best predictions
- Verification by CFD simulation (ANSYS)
 - 2 divergent configurations
 - 2 non-acceptable configurations
 - 3 acceptable configurations (difference < 3%)



| RANK | CONFIGURATION | ERROR[%] |
|------|---------------|----------|
| 1 | CONFIG_2 | 2,37 |
| 2 | CONFIG_5 | 2,74 |
| 3 | CONFIG_15 | 3,12 |
| 4 | CONFIG_4 | 3,88 |
| 5 | CONFIG_1 | 4,46 |
| 6 | CONFIG_8 | 5,11 |
| 7 | CONFIG_14 | 5,29 |
| 8 | CONFIG_11 | 5,90 |
| 9 | CONFIG_7 | 5,95 |
| 10 | CONFIG_13 | 8,01 |
| 11 | CONFIG_9 | 12,25 |
| 12 | CONFIG_12 | 43,98 |
| 13 | CONFIG_3 | 52,70 |
| 14 | CONFIG_10 | 53,96 |
| 15 | CONFIG_6 | 105,91 |

| DIVERGENT SOLUTION | | |
|--------------------|---------------|----------|
| RANK | CONFIGURATION | ERROR[%] |
| 12 | CONFIG_12 | 43,98 |
| 15 | CONFIG_6 | 105,91 |



REFRESH Project – Research Excellence For REgion Sustainability and High-tech Industries,
No. CZ.10.03.01/00/22_003/0000048
is co-financed by the European Union from the Operational Programme Just Transition.

